

标准精度
电阻模块
180种PXI型号,
超过60种PCI型号



标准精度
电阻模块

高功率
电阻模块

标准精度电阻模块 PXI 产品型号 (通道数)		电阻范围								分辨率	准确度*	
		1Ω	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1MΩ	10MΩ			
标准精度电阻模块	40-290-021 (2)	40-290-121 (2+16xSPDT)	可选附加继电器用于扩展阻值范围								0.5Ω	0.5%
	40-291-021 (4)	40-291-121 (4+16xSPDT)									0.5Ω	0.5%
	40-293-011 (4)	40-293-111 (4+8xSPDT)									0.25Ω	0.3%
	40-293-012 (4)	40-293-112 (4+8xSPDT)									0.5Ω	0.3%
	40-293-013 (4)	40-293-113 (4+8xSPDT)									1Ω	0.3%
	40-293-014 (4)	40-293-114 (4+8xSPDT)									2Ω	0.3%
	40-293-021 (2)	40-293-121 (2+8xSPDT)	可选附加继电器, 用于仿真短路和开路								0.25Ω	0.3%
	40-293-022 (2)	40-293-122 (2+8xSPDT)									0.5Ω	0.3%
	40-293-023 (2)	40-293-123 (2+8xSPDT)									1Ω	0.3%
	40-293-024 (2)	40-293-124 (2+8xSPDT)									2Ω	0.3%
	40-293-031 (2)	40-293-131 (2+8xSPDT)									0.25Ω	0.3%
	40-293-032 (2)	40-293-132 (2+8xSPDT)									0.5Ω	0.3%
	40-293-033 (2)	40-293-133 (2+8xSPDT)									1Ω	0.3%
	40-293-034 (2)	40-293-134 (2+8xSPDT)									2Ω	0.3%
	40-294-011 (4)	40-294-111 (4+8xSPST)									0.25Ω	0.3%
	40-294-012 (4)	40-294-112 (4+8xSPST)									0.5Ω	0.3%
	40-294-013 (4)	40-294-113 (4+8xSPST)									1Ω	0.3%
	40-294-014 (4)	40-294-114 (4+8xSPST)									2Ω	0.3%
	40-294-021 (2)	40-294-121 (2+8xSPST)	基于舌簧继电器, 操作速度更快, 使用寿命更长								0.25Ω	0.3%
	40-294-022 (2)	40-294-122 (2+8xSPST)									0.5Ω	0.3%
	40-294-023 (2)	40-294-123 (2+8xSPST)									1Ω	0.3%
	40-294-024 (2)	40-294-124 (2+8xSPST)									2Ω	0.3%
	40-294-031 (2)	40-294-131 (2+8xSPST)									0.25Ω	0.3%
	40-294-032 (2)	40-294-132 (2+8xSPST)									0.5Ω	0.3%
	40-294-033 (2)	40-294-133 (2+8xSPST)									1Ω	0.3%
	40-294-034 (2)	40-294-134 (2+8xSPST)									2Ω	0.3%
	40-295-021-10/8 (10)	40-295-121-18/8 (18)	高密度程控电阻, 参数可定制								1Ω	0.5%
	40-295-021-5/12 (5)	40-295-121-10/12 (10)									1Ω	0.5%
	40-295-021-5/16 (5)	40-295-121-10/16 (10)									1Ω	0.5%
	40-295-021-3/24 (3)	40-295-121-6/24 (6)									1Ω	0.5%
40-296-021-5/8 (5)	40-296-121-9/8 (9)	高密度程控电阻, 参数可定制								1Ω	0.5%	
40-296-021-2/12 (2)	40-296-121-4/12 (4)									1Ω	0.5%	
40-296-021-2/16 (2)	40-296-121-4/16 (4)									1Ω	0.5%	
40-296-021-1/24 (1)	40-296-121-3/24 (3)									1Ω	0.5%	
高功率电阻模块	40-251-110 (4)	40-251-010 (8)	程控电阻, 负载功率2.5W								0.125Ω	0.3%
	40-251-111 (4)	40-251-011 (8)									0.25Ω	0.3%
	40-251-112 (4)	40-251-012 (8)									0.5Ω	0.3%
	40-251-113 (4)	40-251-013 (8)									1Ω	0.3%
	40-251-114 (4)	40-251-014 (8)									2Ω	0.3%
	40-251-120 (2)	40-251-020 (4)									0.125Ω	0.3%
	40-251-121 (2)	40-251-021 (4)									0.25Ω	0.3%
	40-251-122 (2)	40-251-022 (4)									0.5Ω	0.3%
	40-251-123 (2)	40-251-023 (4)									1Ω	0.3%
	40-251-124 (2)	40-251-024 (4)									2Ω	0.3%
	40-251-130 (2)	40-251-030 (4)									0.125Ω	0.3%
	40-251-131 (2)	40-251-031 (4)									0.25Ω	0.3%
	40-251-132 (2)	40-251-032 (4)									0.5Ω	0.3%
	40-251-133 (2)	40-251-033 (4)									1Ω	0.3%
	40-251-134 (2)	40-251-034 (4)									2Ω	0.3%
	40-251-140 (1)	40-251-040 (2)									0.125Ω	0.3%
	40-251-141 (1)	40-251-041 (2)									0.25Ω	0.3%
	40-251-142 (1)	40-251-042 (2)									0.5Ω	0.3%
	40-251-143 (1)	40-251-043 (2)									1Ω	0.3%
	40-251-144 (1)	40-251-044 (2)									2Ω	0.3%
	40-251-150 (1)	40-251-050 (2)									0.125Ω	0.3%
	40-251-151 (1)	40-251-051 (2)									0.25Ω	0.3%
	40-251-152 (1)	40-251-052 (2)									0.5Ω	0.3%
	40-251-153 (1)	40-251-053 (2)									1Ω	0.3%
	40-251-154 (1)	40-251-054 (2)									2Ω	0.3%
	40-252-110 (2)	40-252-010 (4)	程控电阻, 负载功率5W								0.125Ω	0.3%
	40-252-111 (2)	40-252-011 (4)									0.25Ω	0.3%
	40-252-112 (2)	40-252-012 (4)									0.5Ω	0.3%
	40-252-113 (2)	40-252-013 (4)									1Ω	0.3%
	40-252-114 (2)	40-252-014 (4)									2Ω	0.3%
	40-252-120 (1)	40-252-020 (2)									0.125Ω	0.3%
	40-252-121 (1)	40-252-021 (2)									0.25Ω	0.3%
	40-252-122 (1)	40-252-022 (2)									0.5Ω	0.3%
	40-252-123 (1)	40-252-023 (2)									1Ω	0.3%
	40-252-124 (1)	40-252-024 (2)									2Ω	0.3%
	40-252-130 (1)	40-252-030 (2)									0.125Ω	0.3%
	40-252-131 (1)	40-252-031 (2)									0.25Ω	0.3%
	40-252-132 (1)	40-252-032 (2)									0.5Ω	0.3%
	40-252-133 (1)	40-252-033 (2)									1Ω	0.3%
	40-252-134 (1)	40-252-034 (2)									2Ω	0.3%
		40-252-040 (1)									0.125Ω	0.3%
		40-252-041 (1)									0.25Ω	0.3%
		40-252-042 (1)									0.5Ω	0.3%
		40-252-043 (1)									1Ω	0.3%
		40-252-044 (1)									2Ω	0.3%
		40-252-050 (1)									0.125Ω	0.3%
		40-252-051 (1)									0.25Ω	0.3%
		40-252-052 (1)									0.5Ω	0.3%
		40-252-053 (1)									1Ω	0.3%
		40-252-054 (1)									2Ω	0.3%
40-253-110 (1)	40-253-010 (2)	程控电阻, 负载功率10W								0.125Ω	0.3%	
40-253-111 (1)	40-253-011 (2)									0.25Ω	0.3%	
40-253-112 (1)	40-253-012 (2)									0.5Ω	0.3%	
40-253-113 (1)	40-253-013 (2)									1Ω	0.3%	
40-253-114 (1)	40-253-014 (2)									2Ω	0.3%	
	40-253-020 (1)									0.125Ω	0.3%	
	40-253-021 (1)									0.25Ω	0.3%	
	40-253-022 (1)									0.5Ω	0.3%	
	40-253-023 (1)									1Ω	0.3%	
	40-253-024 (1)									2Ω	0.3%	
	40-253-030 (1)									0.125Ω	0.3%	
	40-253-031 (1)									0.25Ω	0.3%	
	40-253-032 (1)									0.5Ω	0.3%	
	40-253-033 (1)									1Ω	0.3%	
	40-253-034 (1)									2Ω	0.3%	
	40-292-011 (1)	程控负载电阻, 最大负载功率15W								1Ω	5%	
	40-292-012 (1)									10Ω	5%	

