



NEW: Humidity Monitoring with LIBERO PDF Logger®

Humidity monitoring associated with controlled room temperature monitoring is becoming a new focus of the pharmaceutical industry and the EU regulators, in particular on sea freight transports or in small storage facilities.

ELPRO is pleased to announce the temperature & humidity version of its LIBERO PDF Logger® that unifies secure cold chain monitoring with the advantages of Adobe's PDF file format.

The groundbreaking concept of producing the report (PDF/A file) within the Datalogger removes the need to install and qualify specific software at destination. LIBERO automatically evaluates alarm criteria and creates a PDF/A report as soon as it is plugged into the USB port of any PC.

These are the additional advantages:

- Alarm limits for temperature & humidity
- High Accuracy in the vital range of -10° to +40°C
- Can be customized within one second by SmartStart Pack&Go
- Connection over USB port, neither data cable nor readout interface necessary
- Optional: Detailed analysis with elproLOG ANALYZE

The LIBERO THi1 temperature & humidity monitor is designed for measuring and recording relative humidity from 10% to 100% RH and temperatures from -25°C to +70°C.

广州虹科电子科技有限公司 广州市五山华南理工大学国家科技园 2 号楼 504-505 室 (510640)

电话 : 020-3874 3030; 3874 3032 e-mail: sales@hkaco.com 网站: www.hkaco.com