

KPA EtherCAT PC104 board (EtherCAT slave stack with PC104 interface) integrates a PC 104 system into an EtherCAT network.

Hardware

- ET 1100 ASIC, no CPU for closer synchronization
- 8 kByte PDO, 8 FMMUs, 8 Sync Managers
- Polling- and IRQ-handling
- DMA - support
- Transfer rate of **2 MByte/s** using DMA and IRQ
- Software-configurable I/O address
- Two address switches for position independent addressing

Slave Stack

- Operating Systems: INtime, Linux, QNX, RTX, xPC Target, VxWorks.
- Several mailbox protocols as CoE, EoE, FoE, SoE, VoE
- Distributed Clocks
- Different scan rates

Applications

- Intelligent slave controller
- Master and slave within one PC104 system (vertical integration)

Delivery package

- PC104 board with compiled KPA EtherCAT Slave stack
- Documentation and sample applications
- One year technical support and assistance in conformance testing included

Ordering information

Product code	Name	Comment
4001 0101	KPA EtherCAT Slave PC 104	
7010 0019	KPA EtherCAT Studio	Configuration and diagnostic tool with integrated master



HongKe



hkaco.com

请通过sales@hkaco.com联系我们

广州：020-3874 3032；13434369840 上海：021-6728 3703 北京：010-5781 5068 西安：029-8187 3816